

RX MARINE INTERNATIONAL

Total Solution Total Protection

AN ISO CERTIFIED COMPANY



Car coating remover (HD)

Part/Order no: Packing

RXSOL-41-4136-25 25 Ltr RXSOL-41-4136-210 210 Ltr

INTRODUCTION:

RXSOL-41-4136 WAS ESPECIALLY DEVELOPED TO REMOVE PROTECTIVE COATINGS AND WAX FROM FOREIGN CARS AND EQUIPMENT THAT HAVE BEEN COATED TO PROTECT THE SURFACE FROM THE ENVIRONMENT WHILE IN TRANSPORTATION FROM FOREIGN COUNTRIES.

RXSOL-41-4136 MAY BE DILUTED WITH MINERAL SPIRITS OR KEROSENE TO REDUCE COSTS.

Application:

MIX 1 PART RXSOL-41-4136 WITH 1-4 PARTS SOLVENT. APPLY TO A NEW CAR WITH A MITT OR A LOW PRESSURE SPRAYER (TANK TYPE SPRAYER). LET SET ON SURFACE FOR 1 TO 5 MINUTES THEN AGITATE. RINSE WITH CLEAR WATER. RXSOL-41-4136 IS SAFE ON METALS AND TENDS TO RETARD CORROSION ON SURFACES.

Note:

DANGER: KEEP OUT OF REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED. CONTAINS PETROLEUM DISTILLATES, DO NOT TAKE INTERNALLY. IF INGESTED-DO NOT INDUCE VOMITING. COMBUSTIBLE LIQUID- KEEP AWAY FROM HIGH HEAT AND OPEN FLAME.



